


# iDISPLAY™ Tablet 15.6" UIT415



The iDISPLAY Tablet 15.6" is designed as an interactive display for any location. Operating on an Android operating system and powered by Pulse technology, this slim and elegant display includes all of the solutions needed for commercial locations. Attach to any standard TV/monitor VESA bracket and simply turn on the power. It is a fully interactive commercial display that uses capacitive touch, built in WiFi and LAN, and a host of integrated features that work in either landscape or portrait format. With the option to expand to 3G services\*, this is an amazing, interactive digital display that creates an engaging, memorable consumer experience.



\*3G Optional, pending carrier compatibility/availability.  
For more information about iDISPLAY Tablets please  
visit our website: [www.outform.com/idisplay](http://www.outform.com/idisplay)

Panel Information	Screen Size	15.6"
	Resolution	1920 x 1080 Pixels
	Brightness	300 cd/m <sup>2</sup>
	Contrast Ratio	700
	Aspect Ratio	16:9
	Active Area Size (WxH)	344.16 x 193.59mm
	Viewing Angle Touch	89°/89°(H), 89°/89°(V)
	Touch Technology	Capacitive G+G 10 point
Hardware and OS	CPU	RK3288, Cortex-A17, up to 1.8GHz Quad Core
	GPU	Mali T764 MP4, 600MHz
	Internal Memory	2GB, DDR3
	Flash Memory	16GB
	Operating System	Android 4.4 / 5.1
	Battery	N/A
	Video/Images	Video Formats
Video Codecs		MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC
Image Formats		JPG/JPEG, PNG, BMP
HDMI Output		N/A
Playback Software		Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infinitely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.
Audio	Speakers	3W x 2
	Audio Codecs	MP3, WMA, AAC, FLAC, WAV
Communications	Bluetooth	4.0
	Wi-Fi	802.11 b/g/n 2.4GHz (AP6212)
	Wired Ethernet	100M/1000M, RJ45
	Wireless 3G	Through internal USB dongle (Optional)
General information	Color	Black (Standard), White (Optional)
	Camera	Front 2MP
	I/O ports	DC, 3.5mm Audio Output Jack, USB 2.0 Host x 2, USB 2.0 OTG x 1, RJ45
	Included in Box	Display Unit, Power Adapter, Power Cable, User Manual, Warranty
	Optional Accessories	Floor stand, Counter stand (L), Shelf clip, Adjustable shelf clip, Wall bracket, Rotating bracket
	Sensors	G-Sensor (3-Axis accelerometer)
	Power Input	12V/3A
	Power Consumption	25W (max)
	Power Over Ethernet	Through RJ45
	Operating Temperature	0-40 °C
	Relative Humidity	85%
	Certifications	Display Unit: ROHS, FCC and CE complaint Power Supply Unit: UL, FCC and CE compliant
Dimensions	Size (L x W x H)	405 x 36 x 254mm
	Product Weight	2.72kg
	Gift Box Size	628 x 89 x 308mm
	Master Carton Size	646 x 196 x 330mm
	Master Carton Weight	7.92kg
	Units per Master Carton	2pcs