

BY OUTFORM...



Product Catalog







Enterprise



4K Media Player



Tower



iShelf



Window Light Show™



Kinetic LED Light Show™

iDISPLAY™ Product Catalog

Introduction

Welcome to the iDISPLAY™ product catalog. This edition will ensure that you have access to a definitive and detailed catalog to our world-class portfolio. Both product sales brochures as well as product specification sheets have been included for your use. Used individually or collectively, this catalog is meant to assist you in the marketing and sales of iDISPLAY™ to your clients. The electronic catalogue is navigable and will provide you all iDISPLAY™ product information at the touch of a click.

For pricing or more detailed product information, please contact your local iDISPLAY™ sales representative or contact us at www.outform.com/contact

iDISPLAY™

The iDISPLAY™ brand of touch screen tablets and displays is a wholly owned subsidiary of Outform. iDISPLAY™ utilizes proprietary technology and industrial grade materials for maximum performance in commercial environments. From supermarkets to restaurants to apparel retail, we study every aspect of your business to determine how our solutions can help you create new sources of customer value and competitive differentiation.

OUTFORM

Outform is a full-service, brand implementation firm that delivers innovation to store environments that both excite and incite shoppers. We enhance brand presence through creative, intelligent solutions that inspire behavior and motivate purchase. From ideation & discovery to design & deployment, our teams produce impactful solutions that generate brand equity, advocacy and Return on Investment. Specializing in both complex retail executions and in retail-ready interactive kiosks, Outform creates engaging, disruptive displays with state of the art technologies that support in-store activation and drive sales.

USA

Outform, Inc. (East Coast) 261 NE 1st Street, Miami, FL 33132, USA +1.800.204.0524 www.outform.com

UK

Outform Ltd.
Millennium House, Humber Road, London
NW2 6DW, United Kingdom
+44 (0) 845.4606.111

iDISPLAY[™] Product Line

iDISPLAY™	Tablet 7"	.11
iDISPLAY™	Tablet 10.1"	.12
iDISPLAY™	Tablet 13.3"	.13
iDISPLAY™	Tablet 15.6"	.14
iDISPLAY™	Tablet 18.5"	.15
iDISPLAY™	Tablet 21.5"	.16
iDISPLAY™	Tablet 24"	.17
iDISPLAY™	Tablet 27"	.18
iDISPLAY™	Tablet 32"	.19
iDISPLAY™	Tablet 43"	.20
iDISPLAY™	Tablet 55"	.21
iDISPLAY™	Ad Display 15.6"	.23
iDISPLAY™	Ad Display 18.5"	.24
iDISPLAY™	Ad Display 21.5"	.25
iDISPLAY™	Enterprise	.28
iDISPLAY™	4K Media Player	31
iDISPLAY™	Tower	33
iDISPLAY™	iShelf 2.	35
Window Lig	ght Show™	36
Kinetic LED	Light Show™	39

iDISPLAY™ Interactive Tablets

7" 10.1" 13.3" 15.6" 18.5" 21.5" 24" 27" 32" 43" 55"



Interactive tablets serve to educate customers about a retailer's latest products, guests about their hotel's services or employees about their company's most recent events, while ensuring that messaging across the various communication channels and multiple locations remains current, consistent and most importantly, personalized. Operating on Android OS, iDisplay™ provides a broad portfolio of tablets that run looping and static marketing media as well as various content applications that attract, engage and inform your customers on your products & services.







Tablet Features

- Sizes: 7", 10.1", 13" 15", 18", 21", 24", 27" 32"
- Lightweight design
- Multi-touch screen
- WiFi
- Versatile display options

Pulse Management**

Tablet administrator, remote content and Mobile Device Management (MDM) for cloud based device management, applications, security and analytics

**subscription based

Business Applications

Multiple ports and peripheral options to expand display functionality for target marketing, mobile POS and consumer engagement metrics



3G Modem USB dongle

Mobile broad band internet connectivity for location based advertising and device tracking



Screen Orientation

Tablets operate in both portrait and landscape modes to deliver a host of unique consumer experiences

Fixtures

Counter stands, floor stands, wall, shelf and table brackets





















995.28mm 39.18" 55.60mm 2.19" VESA 400mm 23.31"



Tabelt Screen Size		7"	10.1"	13.3"	15.6"	18.5"	21.5"	
Model Number		UIT407B-B01	UIT410B-B01	UIT413B-B01	UIT415B-B01	UIT418B-B01	UIT421B-B01	
Panel Information	Resolution	1024 x 600 Pixels	1280 x 800 Pixels	1920 x 1080 Pixels	1920 x 1080 Pixels	1366 x 768 Pixels	1920 x 1080 Pixels	
	Brightness	400 cd/m ²	300 cd/m²	300 cd/m ²	300 cd/m ²	250 cd/m²	250 cd/m ²	
	Contrast Ratio	900	900	1000	800	1000	3000	
	Aspect Ratio					16:9		
	Active Area Size (W x H)	153.6 x 90mm	216.96 x 135.6mm	293.76 x 165.24mm	344.16 x 193.59mm	409.8 x 230.4mm	476.64 x 268.11mm	
	Viewing Angle Touch	80°/80°/80°/80°	80°/80°/80°/80°	90°/90/90°/90°	70°/70°/60°/60°	85°/85°/80°/80°	89°/89°/89°/89°	
	Touch Technology	Capacitive G+G, 5 point	Capacitive G+G 10 point	Capacitive G+G, 10 point	Capacitive G+G, 10 point	Capacitive G+G, 10 point	Capacitive G+G, 10 point	
Hardware and OS	CPU	RK3188, Cortex-A9, up to 1.6GHz Quad Core	RK3188, Cortex-A9, up to 1.6GHz Quad Core	RK3188, Cortex-A9, up to 1.6GHz Quad Core	RK3288, Cortex-A, up to 1.8 GHz Quad Core	RK3288, Cortex-A9, up to 1.8GHz Quad Core	RK3288, Cortex-A17, up to 1.8GHz Quad Core	
	GPU	Mali 400 MP4, 600MHz	Mali 400 MP4, 600MHz	Mali 400 MP4, 600MHz	Mali T764 MP4, 600MHz	Mali T764	Mali T764	
	Internal Memory	1GB, DDR3	1GB, DDR3	1GB, DDR3	2GB, DDR3	2GB, DDR3	2GB, DDR3	
	Flash Memory	8GB	8GB	16GB	16GB	16GB	16GB	
	Operating System	Android 4.4 / 5.0						
	Battery	No Battery (Standard), Li 3.7V 7800mAh (Optional)	No Battery (Standard), Li 3.7V 7800mah (Optional)	Option 1: Li 3.7V 5000*2/ 10000MAH Option 2:	N/A	N/A	N/A	
				RTC Battery				
Video/Image	Video Formats			3GP, MP4, AVI, MKV, I	FLV, MOV, RM, RMVB			
	Video Codecs		М	PG-1, MPG-2, MPG-4, H.263, I	H.264, VC-1, RV, VP6/VP8, MVC			
	Image Formats			JPG, JPEG,	PNG, BMP			
	HDMI Output	N/A	Mini HDMI	Mini HDMI	N/A	N/A	N/A	
	Playback Software	Built-in software allows for ea auto-started upon boot-up	sy setup of a playlist of video	s and/or stills which can be lo	oped infinitely without any addi	tional software. Alternatively, an	ny installed app can be	
Audio	Speakers	1W x 2	1W x 2	2W x 2	3W x 2	3W x 2	2W x 2	
	Audio Codecs			MP3, WMA, AA	AC, FLAC, WAV			
Communications	Bluetooth			4.	0			
	Wi-Fi	802.11 b/g/n 2.4GHz	802.11 b/g/n 2.4GHz	802.11 b/g/n 2.4GHz	802.11 b/g/n 2.4GHz	802.11 b/g/n 2.4GHz	802.11 b/g/n 2.4GHz	
	Wired Ethernet	100M/1000MHz, RJ45	100M/1000M, RJ45	100M/1000M through external USB dongle (Optional)	100M/1000MHz, RJ45, Internal	100M/1000M	100M/1000M	
	Wireless 3G	(TBD)	Through internal Mini- PCIE card (Optional)	Through external USB dongle (Optional)	Through internal USB dongle (Optional)	Through external USB dongle (Optional)	Through internal USB dongle (Optional)	
General Information	Color	Black	Black	Black (Standard), White (Optional)	Black (Standard), White (Optional)	Black (Standard), White (Optional)	Black (Standard), White (Optional)	

Tabelt Screen Size		7"	10.1"	13.3"	15.6"	18.5"	21.5"
Model Number		UIT407B-B01	UIT410B-B01	UIT413B-B01	UIT415B-B01	UIT418B-B01	UIT421B-B01
General nformation	Color	Black	Black	Black (Standard), White (Optional)	Black (Standard), White (Optional)	Black (Standard), White (Optional)	Black (Standard), White (Optional)
	Camera	No Camera (Standard), 8MP (Optional)	No Camera (Standard), 8MP (Optional)	N/A	Front 2MP	Front 2MP	Front 2MP
	I/O Ports	DC, Micro SD, Microphone, 3.5mm Audio Output Jack, USB 2.0 Host x 1, USB 2.0 OTG x 1, RJ45	DC, Micro SD, Mini HDMI, SIM, Microphone, 3.5mm Audio Output Jack, USB 2.0 Host x 1, USB 2.0 OTG x 1, RJ45	DC, SD/TF Card, mini HDMI, Microphone, 3.5mm Audio Output Jack, USB 2.0 Host x 1, USB 2.0 OTG x 1	DC, Earphones, RJ45, USB Host x 2, USB OTG	DC, 3.5mm Audio Output jack, USB 2.0 Host x 1, USB 2.0 Host x1, USB 2.0 OTG x 1, RJ45	DC, 3.5mm Audio Outpu Jack, USB 2.0 Host x 1, US 2.0 OTG x 1, RJ45
	Included in Box	Display Unit, Power Adapter, Power Cable, VISA 40mm to 75mm Bracket, User Manual, Warranty	Display Unit, Power Adapter, Power Cable, User Manual, Warranty	Display Unit, Power Adapter, Power Cable, User Manual, Warranty	Display Unit, Power Adapter, Power Cable, User Manual, Warranty	Display Unit, Power Adapter, Power Cable, User Manual, Warranty	Display Unit, Power Adapter, Power Cable, Us Manual, Warranty
	Optional Accessories	Floor stand, Counter stand (S), Shelf clip, Adjustable shelf clip, Wall bracket, Rotating bracket	Floor stand, Counter stand (S), Shelf clip, Adjustable shelf clip, Wall bracket, Rotating bracket	Floor stand, Counter stand (L), Shelf clip, Adjustable shelf clip, Wall bracket, Rotating bracket	Floor stand, Counter stand (L), Shelf clip, Adjustable shelf clip, Wall bracket, Rotating bracket	Floor stand, Counter stand (L), Shelf clip, Adjustable shelf clip, Wall bracket, Rotating bracket	Floor stand, Counter star (L), Shelf clip, Adjustable shelf clip, Wall bracket, Rotating bracket
	Sensors	G-Sensor (3-Axis accelerometer)	G-Sensor (3-Axis accelerometer)	G-Sensor (3-Axis accelerometer)	G-Sensor (3-Axis accelerometer)	G-Sensor (3-Axis accelerometer)	G-Sensor (3-Axis accelerometer)
	Power Input	12V/2A	12V/2A	12V/3A	12V/3A	12V/3A	12V/3A
	Power Consumption	10W (max)	14W (max)	12W (max)	25W (max)	25W (max)	30W (max)
	Power Over Ethernet	Through RJ45	Through RJ45	N/A	Through RJ45	N/A	N/A
	Operating Temperature			0-4	0 ℃		
	Relative Humidity			85	5%		
	Certifications	Display Unit: ROHS, FCC and CE complaint	Display Unit: ROHS, FCC and CE complaint	Display Unit: ROHS, FCC and CE complaint	Display Unit: ROHS, FCC and CE complaint	Display Unit: ROHS, FCC and CE complaint	Display Unit: ROHS, FCC and CE complaint
		Power Supply Unit: UL, FCC and CE compliant	Power Supply Unit: UL, FCC and CE compliant	Power Supply Unit: UL, FCC and CE compliant	Power Supply Unit: UL, FCC and CE compliant	Power Supply Unit: UL, FCC and CE compliant	Power Supply Unit: UL, Frand CE compliant
		Battery and RTC Battery: UL and UN38.3 compliant	Battery: UL and UN38.3 compliant	Battery and RTC Battery: UL and UN38.3 compliant			
Dimensions	Size (L x W x H)	192 x 26 x 124.5mm	258.77 x 32.8 x 175.47mm	340 x 25 x 220mm	405 x 36 x 254mm	460 x 32 x 280mm	536 x 35 x 328mm
	Product Weight	0.46kg	0.78kg	1.48kg	2.72kg	4.53kg	4.8kg
	Gift Box Size	264 x 22 8 x 80mm	400 x 225 x 69.5mm	388 x 78 x 318mm	628 x 308 x 89mm	678 x 110 x 348mm	756 x 99 x 393mm
	Master Carton Size	420 x 280 x 250mm	420 x 230 x 250mm	410 x 410 x 340mm	646 x 330 x 196mm	693 x 355 x 375mm	774 x 415 x 261mm
	Master Carton Weight	6kg	4.33kg	12kg	7.92kg	14.7kg	15.23kg
	Units per Master Carton	5pcs	3pcs	5pcs	2pcs	3pcs	2pcs

Tabelt Screen Size		24"	27"	32"	43"	55"	
Model Number		UIT424B-B01	UIT427B-B01	UIT432B-B01	UIT443B-B01	UIT455B-B01	
Panel Information	Resolution	1920 x 1080 Pixels	1920 x 1080 Pixels	1920 x 1080 Pixels	1920 x 1080 Pixels	1920 x 1080 Pixels	
	Brightness	250 cd/m ²	250 cd/m ²	250 cd/m ²	300 cd/m ²	305 cd/m ²	
	Contrast Ratio	1000	1000	3000	1200	4000	
	Aspect Ratio				16:9		
	Active Area Size (W x H)	527.2 x 296.67mm	579.6 x 336.15mm	698.4 x 392.85mm	942.20 x 530.4mm	1207.60 x 678.40mm	
	Viewing Angle Touch	85°/85°/80°/80°	85°/85°/80°/80°	89°/89°/89°/89°	89°/89°/89°	89°/89°/89°/89°	
	Touch Technology	Capacitive G+G, 10 point	Capacitive G+G, 10 point	Capacitive G+G, 10 point	Capacitive G+G, 10 point	Capacitive G+G, 10 point	
Hardware and OS	CPU	RK3288, Cortex-A9, up to 1.8GHz Quad Core	RK3288, Cortex-A9, up to 1.8GHz Quad Core	RK3288, Cortex-A9, up to 1.8GHz Quad Core	RK3288, Cortex-A17, up to 1.8GHz Quad Core	RK3288, Cortex-A17, up to 1.8GHz Quad Core	
	GPU	Mali 400 MP4, 600MHz	Mali 400 MP4, 600MHz	Mali 400 MP4, 600MHz			
	Internal Memory	2GB, DDR3	2GB, DDR3	2GB, DDR3	2GB, DDR3	2GB, DDR3	
	Flash Memory	16GB	16GB	16GB	16GB	16GB	
	Operating System	Android 4.4 / 5.0					
	Battery	N/A	N/A	N/A	N/A	N/A	
Video/Image	Video Formats		3GF	P, MP4, AVI, MKV, FLV, MOV, RM, RMV	/B		
	Video Codecs	MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC					
	Image Formats			JPG, JPEG, PNG, BMP			
	HDMI Output	N/A	N/A	N/A	Yes	Yes	
	Playback Software		etup of a playlist of videos and/or stills ftware. Alternatively, any installed ap				
Audio	Speakers	3W x 2	3W x 2	3W x 2	5W x 2	5W x 2	
	Audio Codecs			MP3, WMA, AAC, FLAC, WAV			
Communications	Bluetooth			4.0			
	Wi-Fi	802.11 b/g/n 2.4GHz	802.11 b/g/n 2.4GHz	802.11 b/g/n 2.4GHz	802.11 b/g/n 2.4GHz	802.11 b/g/n 2.4GHz	
	Wired Ethernet	100M/1000M	100M/1000M	100M/1000M	10M/100M	10M/100M	
	Wireless 3G	Through external USB dongle (Optional)	Through external USB dongle (Optional)	Through external USB dongle (Optional)	Through external USB dongle (Optional)	Through external USB dongle (Optional)	

Tabelt Screen Size		24"	27"	32"	43"	55"			
Model Number		UIT424B-B01	UIT427B-B01	UIT432B-B01	UIT443B-B01	UIT455B-B01			
General Information	Color	Black (Standard), White (Optional)	Black (Standard), White (Optional)	Black (Standard), White (Optional)	Black (Standard), White (Optional)	Black (Standard), White (Optional)			
	Camera	Front 2MP	Front 2MP	N/A	Front 5MP	N/A			
	I/O Ports	DC, 3.5mm Audio Output Jack, USB 2.0 Host x 3, mini USB 2.0 OTG x 1, RJ45	DC, 3.5mm Audio Output Jack, USB 2.0 Host x 3, mini USB 2.0 OTG x 1, RJ45	DC, 3.5mm Audio Output Jack, USB 2.0 Host x 1, USB 2.0 OTG x 1, RJ45	SD, 3.5mm Audio Output Jack, USB 2.0 OTG x 1, USB 2.0 HOST x 2, HDMI, DC	SD, 3.5mm Audio Output Jack, USB 2.0 OTG x 1, USB 2.0 HOST x 2, HDMI, DC			
	Included in Box	Display Unit, Power Adapter, Power Cable, User Manual, Warranty	Display Unit, Power Adapter, Power Cable, User Manual, Warranty	Display Unit, Power Adapter, Power Cable, User Manual, Warranty	Display Unit, Power Adapter, Power Cable, User Manual, Warranty	Display Unit, Power Adapter, Power Cable, User Manual, Warranty			
	Optional Accessories	Floor stand, Counter stand	Floor stand, Counter stand	Floor stand, Counter Stand					
	Sensors	G-Sensor (3-Axis accelerometer)	G-Sensor (3-Axis accelerometer)	G-Sensor (3-Axis accelerometer)	G-Sensor (3-Axis accelerometer)	G-Sensor (3-Axis accelerometer)			
	Power Input	12V/4A	12V/4A	12V/5A	AC100-240V	AC100-240V			
	Power Consumption	35W (max)	40W (max)	50W (max)		14W (max)			
	Power Over Ethernet	N/A	N/A	N/A	N/A				
	Operating Temperature	0-40 °C							
	Relative Humidity			85%					
	Certifications	Display Unit: ROHS, FCC and CE complaint	Display Unit: ROHS, FCC and CE complaint	Display Unit: ROHS, FCC and CE complaint	Display Unit: ROHS, FCC and CE complaint	Display Unit: ROHS, FCC and CE complaint			
		Power Supply Unit: UL, FCC and CE compliant	Power Supply Unit: UL, FCC and CE compliant	Power Supply Unit: UL, FCC and CE compliant	Power Supply Unit: UL, FCC and CE compliant	Power Supply Unit: UL, FCC and CE compliant			
Dimensions	Size (L x W x H)	580 x 35.8 x 349.2mm	654 x 33.5 x 394.2mm	750 x 60 x 450mm	995.28 x 592.14 x 55.6mm	1263.18 x 747.28 x 56.5mm			
	Product Weight	5.9kg	6.95kg	8.03kg	18.1kg	29kg			
	Gift Box Size	310 x 110 x 447mm	680 x 120 x 501mm	862 x 135 x 555mm	1156 x 792 x 160mm				
	Master Carton Size	330 x 135 x 473mm	700 x 145 x 526mm	880 x 150 x 580mm	1180 x 817 x 178mm				
	Master Carton Weight	10.5kg	12.5kg	14.4kg	20.1kg				
	Units per Master Carton	1рс	1рс	1pc	1pcs	1pcs			

Panel Information	Screen Size	7"
rancemioniación	Resolution	1024 x 600 Pixels
	Brightness	400 cd/m ²
	Contrast Ratio	900
	Aspect Ratio	16:9
	Active Area Size (WxH)	153.6 x 90mm
	Viewing Angle Touch	80°/80°/80°
	Touch Technology	Capacitive G+G, 5 point
Hardware and OS	CPU	RK3188, Cortex-A9, up to 1.6GHz Quad Core
	GPU	Mali 400 MP4, 600MHz
	Internal Memory	1GB, DDR3
	Flash Memory	8GB
	Operating System	Android 4.4 / 5.0
	Battery	No Battery (Standard), Li 3.7V 7800mAh (Optional)
Video/Images	Video Formats	3GP, MP4, AVI, MKV, FLV, MOV, RM, RMVB
	Video Codecs	MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC
	Image Formats	JPG, JPEG, PNG, BMP
	HDMI Output	N/A
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infini ely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.
Audio	Speakers	1W x 2
	Audio Codecs	MP3, WMA, AAC, FLAC, WAV
Communications	Bluetooth	4.0
	Wi-Fi	802.11 b/g/n 2.4GHz
	Wired Ethernet	100M/1000MHz, RJ45
	Wireless 3G	(TBD)
General information	Color	Black
	Camera	No Camera (Standard), 8MP (Optional)
	I/O ports	DC, Micro SD, Microphone, 3.5mm Audio Output Jack, USB 2.0 Host x 1, USB 2.0 OTG x 1, RJ45
	Included in Box	Display Unit, Power Adapter, Power Cable, VISA 40mm to 75mm Bracket, User Manual, Warranty
	Optional Accessories	Floor stand, Counter stand (S), Shelf clip, Adjustable shelf clip, Wall bracket, Rotating bracket
	Sensors	G-Sensor (3-Axis accelerometer)
	Power Input	12V/2A
	Power Consumption	10W (max)
	Power Over Ethernet	Through RJ45
	Operating Temperature	0-40 °C
	Relative Humidity	85%
	Certification	Display Unit: ROHS, FCC and CE complaint Power Supply
	Cerementon	Unit: UL, FCC and CE compliant Battery and RTC Battery: UL and UN38.3 compliant
Dimensions	Size (L x W x H)	192 x 26 x 124.5mm
	Product Weight	0.46kg
	Gift Box Size	264 x 228 x 80mm
	Master Carton Size	420 x 280 x 250mm
	Master Carton Weight	6kg
	Units per Master Carton	5pcs
		<u>'</u>

Panel Information	Screen Size	10.1"
r driet information	Resolution	1280 x 800 Pixels
		300 cd/m ²
	Brightness	
	Contrast Ratio	900
	Aspect Ratio	16:9
	Active Area Size (WxH)	216.96 x 135.6mm
	Viewing Angle Touch	80°/80°/80°
	Touch Technology	Capacitive G+G 10 point
Hardware and OS	CPU	RK3188, Cortex-A9, up to 1.6GHz Quad Core
	GPU	Mali 400 MP4, 600MHz
	Internal Memory	1GB, DDR3
	Flash Memory	8GB
	Operating System	Android 4.4 / 5.1
	Battery	No Battery (Standard), Li 3300/3=9900mAh (Optional)
Video/Images	Video Formats	3GP, MP4, AVI, MKV, FLV, MOV, RM, RMVB
	Video Codecs	MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC
	Image Formats	JPG, JPEG, PNG, BMP
	HDMI Output	Mini HDMI
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infini ely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.
Audio	Speakers	1W x 2
	Audio Codecs	MP3, WMA, AAC, FLAC, WAV
Communications	Bluetooth	4.0
	Wi-Fi	802.11 b/g/n 2.4GHz
	Wired Ethernet	10M/100M, RJ45
	Wireless 3G	Through internal Mini-PCIE card (Optional)
General information	Color	Black
	Camera	No Camera
	I/O ports	USB 2.0 Host x 3, RJ45, Micro USB 2.0 OTG x 1, 3.5mm Audio Jack, Mini HDMI, DC
	Included in Box	Display Unit, Power Adapter, Power Cable, User Manual, Warranty
	Optional Accessories	Floor stand, Counter stand (S), Shelf clip, Adjustable shelf clip, Wall bracket, Rotating bracket
	Sensors	G-Sensor (3-Axis accelerometer)
	Power Input	12V/2A
	Power Consumption	14W (max)
	Power Over Ethernet	Through RJ45
		0-40 °C
	Operating Temperature	
	Relative Humidity Certification	85% Display Unit POUS FCC and CF complaint
	Certification	Display Unit: ROHS, FCC and CE complaint Power Supply Unit: UL, FCC and CE compliant Battery: UL and UN38.3 compliant
Dimensions	Size (L x W x H)	258.77 x 32.8 x 175.47mm
	Product Weight	0.78kg
	Gift Box Size	400 x 225 x 69.5mm
	Master Carton Size	420 x 230 x 250mm
	Master Carton Weight	4.33kg
	Units per Master Carton	3pcs
	Units per Master Carton	phrs

ereen Size	13.3" 1920 x 1080 Pixels
esolution	1920 x 1080 Pixels
rightness	300 cd/m ²
-	1000
·	16:9
ctive Area Size (WxH)	293.76 x 165.24mm
ewing Angle Touch	90°/90/90°/90°
ouch Technology	Capacitive G+G, 10 point
PU	RK3188, Cortex-A9, up to 1.6GHz Quad Core
PU	Mali 400 MP4, 600MHz
ternal Memory	1GB, DDR3
ash Memory	16GB
perating System	Android 4.4 / 5.1
attery	Option 1: Li 3.7V 5000*2/10000MAH
	Option 2: RTC battery
deo Formats	3GP, MP4, AVI, MKV, FLV, MOV, RM, RMVB
deo Codecs	MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC
nage Formats	JPG, JPEG, PNG, BMP
DMI Output	Mini HDMI
ayback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infini ely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.
peakers	2W x 2
udio Codecs	MP3, WMA, AAC, FLAC, WAV
uetooth	4.0
/i-Fi	802.11 b/g/n 2.4GHz
/ired Ethernet	10M/100M through external USB dongle (Optional)
/ireless 3G	Through external USB dongle (Optional)
olor	Black (Standard), White (Optional)
amera	N/A
O ports	Micro SD, USB 2.0 Host x 1, USB 2.0 OTG x 1, HDMI, DC, 3.5mm Audio Jack
cluded in Box	Display Unit, Power Adapter, Power Cable, User Manual, Warranty
ptional Accessories	Floor stand, Counter stand (L), Shelf clip, Adjustable shelf clip, Wall bracket, Rotating bracket
ensors	G-Sensor (3-Axis accelerometer)
ower Input	12V/3A
	12W (max)
	N/A
	0-40 °C
	85%
	Display Unit: ROHS, FCC and CE complaint
	Power Supply Unit: UL, FCC and CE compliant Battery and RTC Battery: UL, UN38.3
ze (L x W x H)	340 x 25 x 220mm
oduct Weight	1.48kg
ift Box Size	388 x 78 x 318mm
-	410 x 410 x 340mm
aster Carton Size	410 x 410 x 34011111
aster Carton Size aster Carton Weight	12kg
osciepp Fita Fai — idion Cas — pull /i /i /i — pac of Fei pop Fei e — zigo	contrast Ratio spect Ratio spect Ratio ctive Area Size (WxH) ewing Angle Touch such Technology PU eternal Memory perating System strery deo Formats deo Codecs sage Formats DMI Output sayback Software seakers sudio Codecs suetooth i-Fi ired Ethernet ireless 3G Door smera D ports cluded in Box sotional Accessories sensors sover Input sover Consumption sover Over Ethernet perating Temperature selative Humidity ertification ze (L x W x H) oduct Weight

Panel Information	Screen Size	15.6"
Tance information	Resolution	1920 x 1080 Pixels
		300 cd/m ²
	Brightness	
	Contrast Ratio	800
	Aspect Ratio	16:9
	Active Area Size (WxH)	344.16 x 193.59mm
	Viewing Angle Touch	70°/70°/60°/60°
	Touch Technology	Capacitive G+G, 10 point
Hardware and OS	CPU	RK3288, Cortex-A17, up to 1.8GHz Quad Core
	GPU	Mali T764 MP4, 600MHz
	Internal Memory	2GB, DDR3
	Flash Memory	16GB
	Operating System	Android 4.4 / 5.1
	Battery	N/A
Video/Images	Video Formats	3GP, MP4, AVI, MKV, FLV, MOV, RM, RMVB
	Video Codecs	MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC
	Image Formats	JPG, JPEG, PNG, BMP
	HDMI Output	N/A
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infinitely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.
Audio	Speakers	3W x 2
	Audio Codecs	MP3, WMA, AAC, FLAC, WAV
Communications	Bluetooth	4.0
	Wi-Fi	802.11 b/g/n 2.4GHz
	Wired Ethernet	100M/1000MHz RJ45, Internal
	Wireless 3G	Through internal USB dongle (Optional)
General information	Color	Black (Standard), White (Optional)
	Camera	Front 2MP
	I/O ports	3.5mm Audio Jack, RJ45, USB 2.0 Host x 1, USB 2.0 OTG x 1, DC
	Included in Box	Display Unit, Power Adapter, Power Cable, User Manual, Warranty
	Optional Accessories	Floor stand, Counter stand (L), Shelf clip, Adjustable shelf clip, Wall bracket, Rotating bracket
	Sensors	G-Sensor (3-Axis accelerometer)
	Power Input	12V/3A
	Power Consumption	25W (max)
	Power Over Ethernet	Through RJ45
	Operating Temperature	0-40 °C
	Relative Humidity	85%
	•	
	Certifications	Display Unit: ROHS, FCC and CE complaint Power Supply Unit: UL, FCC and CE compliant
Dimensions	Size (L x W x H)	405 x 36 x 254mm
	Product Weight	2.72kg
		628 x 308 x 89mm
	Gift Box Size	020 X 300 X 0711111
	Gift Box Size Master Carton Size	646 x 330 x 196mm

Panel Information	Screen Size	18.5"
	Resolution	1366 x 768 Pixels
	Brightness	250 cd/m²
	Contrast Ratio	1000
	Aspect Ratio	16:9
	Active Area Size (WxH)	409.8 x 230.4mm
	Viewing Angle Touch	
	Touch Technology	85°/85°/80°/80° Capacitive G+G, 10 point
Hardware and OS	CPU	
riai dwaie aild O3	GPU	RK3288, Cortex-A9, up to 1.8GHz Quad Core Mali T764
	Internal Memory	2GB, DDR3
	Flash Memory	16GB
	Operating System	Android 4.4 / 5.1
	Battery	N/A
Video/Images	Video Formats	3GP, MP4, AVI, MKV, FLV, MOV, RM, RMVB
	Video Codecs	MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC
	Image Formats	JPG, JPEG, PNG, BMP
	HDMI Output	N/A
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infinitely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.
Audio	Speakers	3W x 2
	Audio Codecs	MP3, WMA, AAC, FLAC, WAV
Communications	Bluetooth	4.0
	Wi-Fi	802.11 b/g/n 2.4GHz
	Wired Ethernet	100M/1000M
	Wireless 3G	Through external 3G dongle (Optional)
General information	Color	Black (Standard), White (Optional)
	Camera	Front 2MP
	I/O ports	SD, 3.5mm Audio Jack, Mini USB 2.0 OTG x 1, USB 2.0 Host x 3, HDMI, DC, RJ45
	Included in Box	Display Unit, Power Adapter, Power Cable, User Manual, Warranty
	Optional Accessories	Floor stand, Counter stand (L), Shelf clip, Adjustable shelf clip, Wall bracket, Rotating bracket
	Sensors	G-Sensor (3-Axis accelerometer)
	Power Input	12V/3A
	Power Consumption	25W (max)
	Power Over Ethernet	N/A
	Operating Temperature	0-40 °C
	Relative Humidity	85%
	Certifications	Display Unit: ROHS, FCC and CE complaint Power Supply Unit: UL, FCC and CE compliant
Dimensions	Size (L x W x H)	460 x 32 x 280mm
	Product Weight	4.53kg
	Gift Box Size	678 x 110 x 348mm
	Master Carton Size	693 x 355 x 375mm
	_	
Dimensions	Size (L x W x H) Product Weight Gift Box Size	Power Supply Unit: UL, FCC and CE compliant 460 x 32 x 280mm 4.53kg 678 x 110 x 348mm

Panel Information	Causan Cina	
Panel information	Screen Size	21.5"
	Resolution	1920 x 1080 Pixels
	Brightness	250 cd/m ²
	Contrast Ratio	3000
	Aspect Ratio	16:9
	Active Area Size (WxH)	476.64 x 268.11mm
	Viewing Angle Touch	89°/89°/89°
	Touch Technology	Capacitive G+G, 10 point
Hardware and OS	CPU	RK3288, Cortex-A17, up to 1.8GHz Quad Core
	GPU	Mali T764
	Internal Memory	2GB, DDR3
	Flash Memory	16GB
	Operating System	Android 4.4 / 5.1
	Battery	N/A
Video/Images	Video Formats	3GP, MP4, AVI, MKV, FLV, MOV, RM, RMVB
	Video Codecs	MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC
	Image Formats	JPG, JPEG, PNG, BMP
	HDMI Output	N/A
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infini ely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.
Audio	Speakers	2W x 2
	Audio Codecs	MP3, WMA, AAC, FLAC, WAV
Communications	Bluetooth	4.0
	Wi-Fi	802.11 b/g/n 2.4GHz
	Wired Ethernet	100M/1000M
	Wireless 3G	Through internal USB dongle (Optional)
General information	Color	Black (Standard), White (Optional)
	Camera	Front 2MP
	I/O ports	3.5mm Audio Jack, RJ45, USB 2.0 Host x 1, USB 2.0 OTG x 1, DC
	Included in Box	Display Unit, Power Adapter, Power Cable, User Manual, Warranty
	Optional Accessories	Floor stand, Counter stand (L), Shelf clip, Adjustable shelf clip, Wall bracket, Rotating bracket
	Sensors	G-Sensor (3-Axis accelerometer)
	Power Input	12V/3A
	Power Consumption	30W (max)
	Power Over Ethernet	N/A
	Operating Temperature	0-40 °C
	Relative Humidity	85%
	Certification	Display Unit: ROHS, FCC and CE complaint Power Supply Unit: UL, FCC and CE compliant
Dimensions	Size (L x W x H)	536 x 35 x 328mm
	Product Weight	4.8kg
	Gift Box Size	756 x 99 x 393mm
	Master Carton Size	774 x 415x 261mm
	Master Carton Weight	15.23kg
	Units per Master Carton	2pcs

Panel Information	Screen Size	24"
	Resolution	1920 x 1080 Pixels
	Brightness	250 cd/m ²
	Contrast Ratio	1000
	Aspect Ratio	16:9
	Active Area Size (WxH)	527.2 x 296.67mm
	Viewing Angle Touch	85°/85°/80°/80°
	Touch Technology	Capacitive G+G, 10 point
Hardware and OS	CPU	RK3288, Cortex-A9, up to 1.8GHz Quad Core
	GPU	Mali 400 MP4, 600Mhz
	Internal Memory	2GB, DDR3
	Flash Memory	16GB
	Operating System	Android 4.4 / 5.1
	Battery	N/A
Video/Images	Video Formats	3GP, MP4, AVI, MKV, FLV, MOV, RM, RMVB
	Video Codecs	MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC
	Image Formats	JPG, JPEG, PNG, BMP
	HDMI Output	N/A
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infinitely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.
Audio	Speakers	3W x 2
	Audio Codecs	MP3, WMA, AAC, FLAC, WAV
Communications	Bluetooth	4.0
	Wi-Fi	802.11 b/g/n 2.4GHz
	Wired Ethernet	100M/1000M
	Wireless 3G	Through external USB dongle (Optional)
General information	Color	Black (Standard), White (Optional)
	Camera	Front 2MP
	I/O ports	SD, 3.5mm Audio Jack, Mini USB 2.0 OTG x 1, USB 2.0 Host x 2, HDMI, DC, RJ45
	Included in Box	Display Unit, Power Adapter, Power Cable, User Manual, Warranty
	Optional Accessories	Floor stand, Counter Stand
	Sensors	G-Sensor (3-Axis accelerometer)
	Power Input	12V/4A
	Power Consumption	35W (max)
	Power Over Ethernet	N/A
	Operating Temperature	0-40 °C
		85%
	Relative Humidity	6570
	C: E:	Divided Unit POUS FCC and CF completes
	Certifications	Display Unit: ROHS, FCC and CE complaint Power Supply Unit: UL, FCC and CE compliant
Dimensions	Certifications Size (L x W x H)	
Dimensions		Power Supply Unit: UL, FCC and CE compliant
Dimensions	Size (L x W x H)	Power Supply Unit: UL, FCC and CE compliant 580 x 35.8x 349.2mm
Dimensions	Size (L x W x H) Product Weight	Power Supply Unit: UL, FCC and CE compliant 580 x 35.8x 349.2mm 5.9kg
Dimensions	Size (L x W x H) Product Weight Gift Box Size	Power Supply Unit: UL, FCC and CE compliant 580 x 35.8x 349.2mm 5.9kg 310 x 110 x 447mm

Panel Information	Screen Size	27"	
	Resolution	1920 x 1080 Pixels	
	Brightness	250 cd/m ²	
	Contrast Ratio	1000	
	Aspect Ratio	16:9	
	Active Area Size (WxH)	579.6 x 336.15mm	
	Viewing Angle Touch	85°/85°/80°/80°	
	Touch Technology	Capacitive G+G, 10 point	
Hardware and OS	СРИ	RK3288, Cortex-A9, up to 1.8GHz Quad Core	
	GPU	Mali 400 MP4, 600MHz	
	Internal Memory	2GB, DDR3	
	Flash Memory	16GB	
	Operating System	Android 4.4 / 5.1	
	Battery	N/A	
Video/Images	Video Formats	3GP, MP4, AVI, MKV, FLV, MOV, RM, RMVB	
Viaco, iniages	Video Codecs	MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC	
	Image Formats	JPG, JPEG, PNG, BMP	
	HDMI Output	N/A	
	Playback Software		
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infinitely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.	
Audio	Speakers	3W x 2	
	Audio Codecs	MP3, WMA, AAC, FLAC, WAV	
Communications	Bluetooth	4.0	
	Wi-Fi	802.11 b/g/n 2.4GHz	
	Wired Ethernet	100M/1000M	
	Wireless 3G	Through external USB dongle (Optional)	
General information	Color	Black (Standard), White (Optional)	
	Camera	Front 2MP	
	I/O ports	SD, 3.5mm Audio Jack, Mini USB 2.0 OTG x 1, USB 2.0 Host x 2, HDMI, DC, RJ45	
	Included in Box	Display Unit, Power Adapter, Power Cable, User Manual, Warranty	
	Optional Accessories	Floor stand, Counter Stand	
	Sensors	G-Sensor (3-Axis accelerometer)	
	Power Input	12V/4A	
	Power Consumption	40W (max)	
	Power Over Ethernet	N/A	
	Operating Temperature	0-40 °C	
	Relative Humidity	85%	
	Certifications	Display Unit: ROHS, FCC and CE complaint Power Supply Unit: UL, FCC and CE compliant	
Dimensions	Size (L x W x H)	654 x 33.5 x 394.2mm	
	Product Weight	6.95kg	
	Gift Box Size	680 x 120 x 501mm	
	Master Carton Size	700 x 145 x 526mm	
	Master Carton Weight	12.5kg	
	Units per Master Carton	2pcs	
		r.··	

Panel Information	Screen Size	32"		
Tance information	Resolution	1920 x 1080 Pixels		
		250 cd/m ²		
	Brightness			
	Contrast Ratio	3000		
	Aspect Ratio	16:9		
	Active Area Size (WxH)	698.4 x 392.85mm		
	Viewing Angle Touch	89°/89°/89°		
	Touch Technology	Capacitive G+G ,10 point		
Hardware and OS	CPU	RK3288, Cortex-A9, up to 1.8GHz Quad Core		
	GPU	Mali 400 MP4, 600MHz		
	Internal Memory	2GB, DDR3		
	Flash Memory	16GB		
	Operating System	Android 4.4 / 5.1		
	Battery	N/A		
Video/Images	Video Formats	3GP, MP4, AVI, MKV, FLV, MOV, RM, RMVB		
	Video Codecs	MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC		
	Image Formats	JPG, JPEG, PNG, BMP		
	HDMI Output	N/A		
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infiniely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.		
Audio	Speakers	3W x 2		
	Audio Codecs	MP3, WMA, AAC, FLAC, WAV		
Communications	Bluetooth	4.0		
	Wi-Fi	802.11 b/g/n 2.4GHz		
	Wired Ethernet	100M/1000M		
	Wireless 3G	Through external USB dongle (Optional)		
General information	Color	Black (Standard), White (Optional)		
	Camera	N/A		
	I/O ports	SD, 3.5mm Audio Jack, Mini USB 2.0 OTG x 1, USB 2.0 Host x 2, HDMI, DC, RJ45		
	Included in Box	Display Unit, Power Adapter, Power Cable, User Manual, Warranty		
	Optional Accessories	Floor stand, Counter Stand		
	Sensors	G-Sensor (3-Axis accelerometer)		
	Power Input	12V/SA		
	Power Consumption	50W (max)		
	Power Over Ethernet	N/A		
		0-40 °C		
	Operating Temperature			
	Relative Humidity	85%		
	Certification	Display Unit: ROHS, FCC and CE complaint Power Supply Unit: UL, FCC and CE compliant		
Dimensions	Size (L x W x H)	750 x 60x 450mm		
	Product Weight	8.03kg		
	Gift Box Size	862 x 135 x 555mm		
	1			
	Master Carton Size	880 x 150 x 580mm		
	Master Carton Size Master Carton Weight	880 x 150 x 580mm 14.4kg		

Panel Information	Screen Size	43"
	Resolution	1920 x 1080 Pixels
	Brightness	300 cd/m ²
	Contrast Ratio	1200
	Aspect Ratio	16:9
	Active Area Size (WxH)	942.20 x 530.4mm
	Viewing Angle Touch	89°/89°(H), 89°/89°(V)
	Touch Technology	Capacitive G+G 10 point
Hardware and OS	CPU	RK3288, Cortex-A17, up to 1.8GHz Quad Core
riaidware and OS	GPU	Mali T764 MP4,600MHz
		2GB, DDR3
	Internal Memory	•
	Flash Memory	16GB
	Operating System	Android 4.4 / 5.1
	Battery	N/A
Video/Images	Video Formats	3GP, MP4, AVI, MKV, FLV, MOV, RM, RMVB
	Video Codecs	MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC
	Image Formats	JPG/JPEG, PNG, BMP
	HDMI Output	Yes
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infini ely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.
Audio	Speakers	5W x 2
	Audio Codecs	MP3, WMA, AAC, FLAC, WAV
Communications	Bluetooth	4.0
	Wi-Fi	802.11 b/g/n 2.4GHz
	Wired Ethernet	10M/100M
	Wireless 3G	Through external USB dongle (optional)
General information	Color	Black (Standard), White (Optional)
	Camera	Front 5MP
	I/O ports	SD, 3.5mm Audio Output Jack, USB 2.0 OTG x 1, USB 2.0 HOST x 2, HDMI, DC
	Included in Box	Display Unit, Power Adapter, Power Cable, User Manual, Warranty
	Optional Accessories	N?A
	Sensors	G-Sensor (3-Axis accelerometer)
	Power Input	AC100-240V
	Power Consumption	100W
	Power Over Ethernet	N/A
	Operating Temperature	0-50 °C
		85%
	Certification	Display Unit: ROHS, FCC and CE complaint Power Supply Unit: UL, FCC and CE compliant
Dimensions	Size (L x W x H)	995.28 x 592/14 x 55.6mm
	Product Weight	18.1kg
	Gift Box Size	1156 x 792 x 160mm
	Master Carton Size	1180 x 817 x 178mm
	Master Carton Weight	
	_	
Dimensions	Power Consumption Power Over Ethernet Operating Temperature Relative Humidity Certification Size (L x W x H) Product Weight Gift Box Size Master Carton Size	100W N/A 0-50 °C 85% Display Unit: ROHS, FCC and CE complaint Power Supply Unit: UL, FCC and CE compliant 995.28 x 592/14 x 55.6mm 18.1kg 1156 x 792 x 160mm

Panel Information	Screen Size	55"	
Tance information	Resolution	1920 x 1080 Pixels	
		350 cd/m ²	
	Brightness		
	Contrast Ratio	4000	
	Aspect Ratio	16:9	
	Active Area Size (WxH)	1207.60 x 678.40mm	
	Viewing Angle Touch	89°/89°(H), 89°/89°(V)	
	Touch Technology	Capacitive G+G 10 point	
Hardware and OS	CPU	RK3288, Cortex-A17, up to 1.8GHz Quad Core	
	GPU	Mali T764 MP4,600MHz	
	Internal Memory	2GB, DDR3	
	Flash Memory	16GB	
	Operating System	Android 4.4 / 5.1	
	Battery	N/A	
Video/Images	Video Formats	3GP, MP4, AVI, MKV, FLV, MOV, RM, RMVB	
	Video Codecs	MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC	
	Image Formats	JPG/JPEG, PNG, BMP	
	HDMI Output	Yes	
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infini ely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.	
Audio	Speakers	5W x 2	
	Audio Codecs	MP3, WMA, AAC, FLAC, WAV	
Communications	Bluetooth	4.0	
	Wi-Fi	802.11 b/g/n 2.4GHz	
	Wired Ethernet	10M/100M	
	Wireless 3G	Through external USB dongle (optional)	
General information	Color	Black (Standard), White (Optional)	
	Camera	N/A	
	I/O ports	SD, 3.5mm Audio Output Jack, USB 2.0 OTG x 1, USB 2.0 HOST x 2, HDMI, DC	
	Included in Box	Display Unit, Power Adapter, Power Cable, User Manual, Warranty	
	Optional Accessories	N/A	
	Sensors	G-Sensor (3-Axis accelerometer)	
	Power Input	AC100-240V	
	Power Consumption	120W (max)	
	Power Over Ethernet	N/A	
	Operating Temperature	0-50 °C	
	Relative Humidity	85%	
	Certification	Display Unit: ROHS, FCC and CE complaint	
	Certification	Power Supply Unit: UL, FCC and CE compliant	
Dimensions	Size (L x W x H)	L1263.18 x 747.28 x 56.5mm	
	Product Weight	29kg	
	Gift Box Size	N/A	
	Master Carton Size	1020 x 1435 x 175mm	
	Master Carton Weight	32.5kg	
	Units per Master Carton	1pcs	

iDISPLAY™ Advertising Displays

15.6" 18.5" 21.5"



The compact all-in-one Android Advertising Displays are a great solution for brands and retailers to advertise their digital marketing message in a commercial location. Operating on an Android OS and powered by Pulse technology, these compact screens include all the features of a giant Android tablet, without the touch screen capability. These devices are compatible with standard TV/monitor Vesa brackets and are ready out of the box as soon as you turn on the power. With an integrated media player, a host of built-in signage and connectivity options (embedded WiFi, LAN and 3G USB-dongle), these displays are capable of remote updates for your digital signage content. With high viewing angles and a small footprint, it is well suited as a free standing floor or wall display, in portrait and landscape format.



Ad Display 15.6" Model		
Panel Information	Screen Size	15.6"
	Resolution	1920 x 1080 Pixels
	Brightness	300 cd/m ²
	Contrast Ratio	800
	Aspect Ratio	16:9
	Active Area Size (WxH)	344.16 x 193.59mm
	Viewing Angle Touch	70°/70°/60°/60°
Hardware and OS	CPU	RK3288, Cortex-A17, up to 1.8GHz Quad Core
	GPU	Mali T764 MP4, 600MHz
	Internal Memory	2GB, DDR3
	Flash Memory	16GB
	Operating System	Android 4.4 / 5.0
	Battery	N/A
Video/Images	Video Formats	3GP, MP4, AVI, MKV, FLV, MOV, RM, RMVB
-	Video Codecs	MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC
	Image Formats	JPG, JPEG, PNG, BMP
	HDMI Output	N/A
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infinitely
	r tayback sortware	without any additional software. Alternatively, any installed app can be auto-started upon boot-up.
Audio	Speakers	3W x 2
	Audio Codecs	MP3, WMA, AAC, FLAC, WAV
Communications	Bluetooth	4.0
	Wi-Fi	802.11 b/g/n
	Wired Ethernet	100M/1000MHz RJ45, Internal
	Wireless 3G	Through inernal USB dongle (Optional)
General information	Color	Black (Standard), White (Optional)
	Camera	Front 2MP
	I/O ports	DC, Earphones, RJ45, USB Host x 2, USB OTG
	Included in Box	Display Unit, Power Adapter, Power Cable, User Manual, Warranty
	Optional Accessories	Floor stand, Counter stand (L), Shelf clip, Adjustable Shelf clip, Wall bracket, Rotating bracket
	Sensors	G-Sensor (3-Axis accelerometer)
	Power Input	12V/3A
	Power Consumption	25W (max)
	·	
	Power Over Ethernet	Through RJ45
	Operating Temperature	0-40 °C
	Relative Humidity	85%
	Certifications	Display Unit: ROHS, FCC and CE complaint Power Supply Unit: UL, FCC and CE compliant
Dimensions	Size (L x W x H)	405 x 36 x 254mm
	Product Weight	2.72kg
	Gift Box Size	628 x 308 x 89mm
	Master Carton Size	646 x 330 x 196mm
	Master Carton Weight	7.92kg
	Units per Master Carton	2pcs
	·	I · ·

Panel Information	Screen Size	18.5"
	Resolution	1366 x 768 Pixels
	Brightness	250 cd/m²
	Contrast Ratio	1000
	Aspect Ratio	16:9
	Active Area Size (WxH)	409.8 x 230.4mm
	Viewing Angle Touch	85°/85°/80°/80°
	Viewing Angle Touch	83 /83 /80 /80
Hardware and OS	CPU	RK3288, Crtex-A9, up to 1.8GHz Quad Core
	GPU	Mali T764
	Internal Memory	2GB, DDR3
	Flash Memory	16GB
	Operating System	Android 4.4 / 5.0
	Battery	N/A
Video/Images	Video Formats	3GP, MP4, AVI, MKV, FLV, MOV, RM, RMVB
video/iiilages	Video Codecs	MPG-1, MPG-2, MPG-4, H.264, VC-1, RV, VP6/VP8, MVC
	Image Formats	JPG, JPEG, PNG, BMP
	HDMI Output	N/A
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infini ely
	Playback Software	without any additional software. Alternatively, any installed app can be auto-started upon boot-up.
Audio	Speakers	3W x 2
	Audio Codecs	MP3, WMA, AAC, FLAC, WAV
Communications	Bluetooth	4.0
	Wi-Fi	802.11 b/g/n 2.4GHz
	Wired Ethernet	100M/1000M
	Wireless 3G	Through external USB dongle (Optional)
General information	Color	Black (Standard), White (Optional)
	Camera	Front 2MP
	I/O ports	DC, 3.5mm Audio Output Jack, USB 2.0 Host x 1, USB 2.0 OTG x 1, RJ45
	Included in Box	Display Unit, Power Adapter, Power Cable, User Manual, Warranty
	Optional Accessories	Floor stand, Counter stand (L), Shelf clip, Adjustable shelf clip, Wall bracket, Rotating bracket
	Sensors	G-Sensor (3-Axis accelerometer)
	Power Input	12V/3A
	Power Consumption	25W (max)
	Power Over Ethernet	N/A
	Operating Temperature	0-40 °C
	Relative Humidity	85%
	Certification	Display Unit: ROHS, FCC and CE complaint Power Supply Unit: UL, FCC and CE compliant
Dimensions	Size (L x W x H)	460 x 32 x 280mm
	Product Weight	4.53kg
	Gift Box Size	678 x 110 x 348mm
	Master Carton Size	693 x 355 x 375mm
	Master Carton Weight	14.7kg
	Units per Master Carton	3pcs
	Sincs per master earton	Sp.

Panel Information	Screen Size	21.5"
Tance information	Resolution	1920 x 1080 Pixels
	Brightness	250 cd/m ²
	Contrast Ratio	3000
	Aspect Ratio	16:9
	Active Area Size (WxH)	476.64 x 268.11mm
	Viewing Angle Touch	89°/89°/89°
11	CDU	DV2200 Contact A17 contact 10CU n Octob Contact
Hardware and OS	CPU	RK3288, Cortex-A17, up to 1.8GHz Quad Core
	GPU	Mali T764
	Internal Memory	2GB, DDR3
	Flash Memory	16GB
	Operating System	Android 4.4 / 5.0
	Battery	N/A
Video/Images	Video Formats	3GP, MP4, AVI, MKV, FLV, MOV, RM, RMVB
	Video Codecs	MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC
	Image Formats	JPG, JPEG, PNG, BMP
	HDMI Output	N/A
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infini ely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.
Audio	Speakers	2W x 2
	Audio Codecs	MP3, WMA, AAC, FLAC, WAV
Communications	Bluetooth	4.0
	Wi-Fi	802.11 b/g/n 2.4GHz
	Wired Ethernet	100M/1000M
	Wireless 3G	Through internal USB dongle (Optional)
General information	Color	Black (Standard), White (Optional)
	Camera	Front 2MP
	I/O ports	DC, 3.5mm Audio Output Jack, USB 2.0 Host x 1, USB 2.0 OTG x 1, RJ45
	Included in Box	Display Unit, Power Adapter, Power Cable, User Manual, Warranty
	Optional Accessories	Floor stand, Counter stand (L), Shelf clip, Adjustable shelf clip, Wall bracket, Rotating bracket
	Sensors	G-Sensor (3-Axis accelerometer)
	Power Input	12V/3A
	Power Consumption	30W (max)
	Power Over Ethernet	N/A
	Operating Temperature	0-40 °C
	Relative Humidity Certification	85% Display Unit, POUS, FCC and CF complaint
	Certification	Display Unit: ROHS, FCC and CE complaint Power Supply Unit: UL, FCC and CE compliant
Dimensions	Size (L x W x H)	536 x 35 x 328mm
	Product Weight	4.8kg
	Gift Box Size	756 x 99 x 393mm
	Master Carton Size	774 x 415x 261mm
	Master Carton Weight	15.23kg
	Units per Master Carton	2pcs
		,

iDISPLAY™ Enterprise





Equipping businesses and sales associates to serve customers with instant product information, service options or event information, when and where they need it, is the solution iDISPLAYTM Enterprise delivers. The iDISPLAYTM Enterprise is an integrated, portable self-service kiosk, digital concierge and mobile POS (Point of Sale), all-in-one. With its innovative design, user-friendly interface and versatile use, the iDISPLAYTM Enterprise is sure to increase customer engagement with your brand and help convert your consumers into shoppers.







Smart Connection Gesture Technology

Gesture software with NFC (Near Field Communication) for easy docking and release, no key required



Hands-Free

Tablet handle serves as a kickstand to facilitate keyboard use



All-In-One Kiosk

iDISPLAY™ Enterprise integrates hardware, device management and software for a stand-alone, cost-effective solution



Business Applications

Multiple ports and peripheral options to expand display functionality for target marketing, mobile POS and consumer engagement metrics



Pulse Management**

Tablet administrator, remote content and Mobile Device Management (MDM) for cloud based device management, applications, security and analytics

**subscription based



Portable

Tablet comfort-grip handle permits tablet, associate and customer portability

IDISPLAY " Enterprise N	Model Number: UITX310-B	
Panel Information	Screen Size	10.1"
Resolution		1920 x 1200 Pixels
	Brightness	300 cd/m ²
	Contrast Ratio	800
	Aspect Ratio	16:10
	Active Area Size (WxH)	216.516 x 135.6mm
	Viewing Angle Touch	89°/89°/89°
Touch Technology		Capacitive G+G, 10 point
Hardware and OS	CPU	RK3288, Cortex-A17, 1.8GHz Quad Core
riaraware and OS	GPU	
		Mali T764, 600MHz
	Internal Memory	2GB, LPDDR2
	Flash Memory	8GB
	Operating System	Android 4.4.4 Kit Kat
	Battery	8400mAh (charging: 5-6hrs / discharging @ 720: ≥ 6hrs / discharging standby: ≥14 days)
Video/Images	Video Formats	3GP, MP4, AVI, MKV, FLV, MOV, RM, RMVB
	Video Codecs	MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC
	Image Formats	JPG/JPEG, PNG, BMP
	HDMI Output	N/A
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infinitely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.
Audio	Speakers	2W x 2
	Audio Codecs	MP3, WMA, AAC, FLAC, WAV
Communications	Bluetooth	4.0
	Wi-Fi	802.11b/g/n (supports 2.4 GHz)
Wired Ethernet		10M/100M, RJ45
	Wireless 3G	N/A
General information	Color	Black
	Camera	Front 2.0MP / Back 5.0 MP
	I/O ports (Tablet)	3.5mm audio output jack, 16 pin counter stand port
	I/O ports (Stand)	DC, RJ45, USB 2.0 Host x 1, USB 2.0 OTG x 1, 16pin tablet port, NFC card reader
	Included In Box (Tablet)	Display unit, user manual, warranty
	Included In Box (Stand)	Stand unit, user manual, warranty, power supply, 4 NFC cards, rear back port cover, 2 back port cover screws
	Accessories	Security cable
		G-Sensor (3-Axis accelerometer)
	Sensors	
	Power Input (Stand)	12V/3A
	Power Consumption	30W (max)
	Operation Temperature	0-40 °C
	Relative Humidity	85%
	Certifications	Display Unit: FCC, FCC ID and CE compliant Stand Unit: ROHS, FCC and CE compliant Power Supply Unit: UL, FCC and CE compliant Battery: UL and UN38.3 compliant
Dimensions	Size (L x W x H)	261 x 53 x 180mm
(Tablet)	Product Weight	0.82kg
	Gift Box Size	300 x 78 x 225mm
	Master Carton Size	485 x 325 x 420mm
	Master Carton Weight	13kg
	Units per Master Carton	10pcs
Dimensions	Size (L x W x H)	210 x 161 x 197mm
(Stand)	Product Weight	1.65kg
	Gift Box Size	265 x 217 x 251mm
	Master Carton Size	548 x 452 x 272mm
	Master Carton Weight	10.94kg
	Units per Master Carton	4pcs

iDISPLAY™ 4K Media Player





Disruptive, engaging media is reshaping the digital signage industry, and 4K resolution is leading the charge. With four times the resolution capacity compared to that of full HD (High Definition), the iDISPLAYTM 4K Media Player delivers powerful performance in a sleek, compact design. The iDISPLAYTM 4K Media Player connects to all digital signage networks to stream movies, photos and online video (media) over a wired or wireless network.

Pulse Management provides a tablet/player administrator, device manager and CMS (content management system) to configure display settings and content management for consistent, controlled and branded user experiences across thousands of displays from a single dashboard. Pulse's remote monitoring service ensures that devices are powered up and secured, guarantees that content is deployed and running and that store associates are focused on selling.

Play your media or content applications on any screen anywhere.







 $iDISPLAY^{\tiny{\text{TM}}}\ 4K\ Media\ Player\ transforms\ your\ business\ and\ positions\ the\ consumer\ at\ the\ center\ of\ your\ brand\ experience.$



4K Resolution

- Cinema standard resolution for digital signage & video
- Superior graphic performance
- Configurable to play all video, no cropping or stretching



Pulse Management**

Tablet administrator, remote content and Mobile Device Management (MDM) for cloud based device management, applications, security and analytics

**subscription based



Digital Signage

- Digital signage and video extension applications
- 4K ecosystem/screen interoperability
- CMS (Content Management System) friendly



- Quad Core
- HDMI, WiFi, Ethernet, 3G*
- Built-in memory
- Small footprint



Business Applications

USB port to interface with external portable devices and peripheral options to expand player functionality





Hardware and OS	CPU	RK3288, Cortex-A17, 1.8GHz Quad Core
	GPU	Mali T764, 600MHz
	Internal Memory	2GB, DDR3
	Flash Memory	8GB
	Operating System	Android 4.4.2 Kit Kat
	Battery	N/A
Video/Images	Video Formats	3GP, MP4, AVI, MKV, FLV, MOV, RM, RMVB
	Video Codecs	MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC
	Image Formats	JPG/JPEG, PNG, BMP
	HDMI Output	Supports 4K output (H.264 @ 25 FPS, H.265 @ 30 FPS)
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infinitely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.
Audio	Speakers	N/A
	Audio Codecs	MP3, WMA, AAC, FLAC, WAV
Communications	Bluetooth	4.0
	Wi-Fi	802.11b/g/n (supports 2.4 GHz)
	Wired Ethernet	10M/100M, RJ45
	Wireless 3G	Through external USB dongle (optional)
General information	Color	Black
	Camera	N/A
	I/O ports	DC, micro SD, HDMI, AV, RJ45, USB 2.0 Host x 1, USB 2.0 OTG x 1, optical
	Included in Box	Player unit, power adapter, power cables, user manual, warranty, mini mouse
	Accessories	N/A
	Sensors	N/A
	Power Input	5V/2A
	Power Consumption	6W (max)
	Operation Temperature	0-40 °C
	Relative Humidity	85%
	Certifications	Player Unit: FCC, FCC ID and CE compliant Power Supply Unit: UL, FCC and CE compliant
Dimensions	Size (L x W x H)	132.5 x 31.3 x 103.1mm
	Product Weight	0.27Kg
	Gift Box Size	260 x 58 x 225mm
	Master Carton Size	475 x 290 x 325mm
	Master Carton Weight	9.4kg
	Units per Master Carton	10pcs

iDISPLAY™ Tower



Maximize the effectiveness of your retail merchandising with the Tower from iDISPLAY™. The Tower is an attractive, customizable free-standing display designed to bring your product to life through both product exposition and digital media. Your product commands presence, showcased in a beautiful transparent case housed above a large, 38″ ultra-bright LCD. Run various forms of digital media for advertising campaigns, product introductions or seasonal promotions. Create life-sized imagery to attract and engage your customers, build brand awareness and stand out from the competition. The display may also be branded with your logo or product markings. Content may be changed as often as you like, extending the life of your display while keeping your brand fresh in the eyes of your consumer.

Panel Information	Screen Size	38"
Tance information	Resolution	1920 x 502 Pixels
	Brightness	
	Contrast Ratio	1000 cd/m ²
		7000
	Aspect Ratio	16:4.2
	Active Area Size (WxH)	243.2 x 930.2mm
	Viewing Angle Touch	89°/89°/89°
	Touch Technology	N/A
Hardware and OS	CPU	ARM, Cortex-A9, 1GHz Quad Core
	GPU	N/A
	Internal Memory	1GB, DDR3
	Flash Memory	8GB
	Operating System	Android 4.0.4
	Battery	N/A
Video/Images	Video Formats	AVI, MPEG/MPG, ASF, MOV, MP4
	Video Codecs	MPG-1, MPG-2, MPG-4, H.264, XVID
	Image Formats	JPG/JPEG, PNG, BMP
	HDMI Output	N/A
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infinitely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.
Audio	Speakers	N/A
	Audio Codecs	MP3, MP4, 3GP, AAC, WAV
Communications	Bluetooth	2.1
	Wi-Fi	802.11b/g/n
	Wired Ethernet	10M/100M, RJ45
	Wireless 3G	N/A
General information	Color	Black, White
	Camera	N/A
	I/O ports	DC, 3.5mm audio output jack, RJ45, USB 2.0 Host x 1, USB 2.0 OTG x 1, 6 pin for "Connect Box" (optional)
	Included in Box	Tower unit, power adapter, power cables, user manual, warranty
	Accessories	N/A
	Sensors	N/A
	Power Input	12V/5A
		60W (max)
	Power Consumption Operation Temperature	0-40 °C
	·	40-70%
	Relative Humidity	Display Unit: ROHS, FCC and CE compliant
	Certifications	Power Supply Unit: UL, FCC and CE compliant
Dimensions	Size (L x W x H)	400 x 400 x 1423mm
	Product Weight	43kg
	Gift Box Size	540 x 470 x 1730mm
	Master Carton Size	Individual units shipped
	Master Carton Weight	73kg
	ı "	

iDISPLAY™ iShelf 2



The iSHELF 2 is a 7" interactive digital shelf-talker used to attract and communicate with customers as they shop in aisle throughout the store. Attached to the edge of the shelf, this compact display may be branded and used to advertise a special sale, introduce a new product or marketing campaign or share other product information through static images or video messaging. The iSHELF 2 is an effective tool that draws attention and invites participation with your brand at shelf, breaking through much of the visual noise that occurs in the last three feet of the sale. Battery power as an option, the iSHELF 2 does not require a dedicated power source and can be placed virtually anywhere throughout the store. Display deployment and media uploads are so simple, an iSHELF 2 program may be managed by store associates, eliminating the need for technical installation and support.

Panel Information	Screen Size	7"
ranetimonnation	Resolution	7 800 × 480
	Brightness	250 cd/m ²
	Contrast Ratio	500
	Aspect Ratio	16:9
	Active Area Size (WxH)	154.08 x 85.92mm
	Viewing Angle Touch	50°/70°/70°
	Touch Technology	N/A
Hardware and OS	CPU	Samsung Q248
	GPU	N/A
	Internal Memory	1GB, DRAM
	Flash Memory	N/A
	Operating System	N/A
	Battery	D cell batteries x 8 (not included)
Video/Images	Video Formats	MPEG-1, MPEG-2, MPEG-4
	Video Codecs	XVID, DIVX 4, DIVX 5
	Image Formats	JPG/JPEG, BMP
	HDMI Output	N/A
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infinitely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.
Audio	Speakers	1.5W x 2
	Audio Codecs	MP3, WMA, WAV
Communications	Bluetooth	N/A
	Wi-Fi	N/A
	Wired Ethernet	N/A
	Wireless 3G	N/A
General information	Color	Silver (Standard), Red (Optional), Black (Optional) and Customized
	Camera	N/A
	I/O ports	DC, USB 2.0 Host x 1
	Included in Box	Shelf display unit, power adapter, power cables, user manual, warranty,
	Accessories	iSHELF clip
	Sensors	N/A
	Power Input	5V/1.5A
	Power Consumption	5W (max)
	Operation Temperature	0-40 °C
	Relative Humidity	40-70%
	Certifications	Display Unit: ROHS, FCC and CE compliant Power Supply Unit: FCC and CE compliant
Dimensions	Size (L x W x H)	360 x 74 x 114mm
	Product Weight	0.85kg
	Gift Box Size	482 x 156 x 118mm
	Master Carton Size	612 x 495 x 340mm
	Master Carton Weight	18.5kg
	Units per Master Carton	10.5kg
	Onits per Master Carton	10pc

Window Light Show™



Create customer excitement through a stunning visual experience in your store front or retail window. The WLS (Windows Light Show™) is unique LED signage that can drive traffic, promote your brand or simply create retail ambiance to enhance customer experience. A great vehicle for brands to tell their story in a unique way, The Windows Light Show™ breaks through random messaging that competes for customers' attention in store. Unlike video walls, this large light canvas is transparent and does not obstruct store merchandising and can be viewed from all angles, in and outside of the store. Retailers today need to make their store campaigns more compelling than ever before. The Windows Light Show™ may be the answer to the customer attraction you are looking for.

Video Wall or Window Light Show™ for your next campaign?

Purchase Considerations	Video Wall	Window Light Show™
Campaign ROI (Return on Investment)	×	√
Transparent merchandising	×	✓
Customizable size	×	✓
Visible in and outside of store	×	√
Text and ambient messaging	1	✓
HD (High Definition) messaging	1	×
Increase sales & brand awareness	1	√



Store EnvironmentsMultiple sizes and form factors to fit every retail environment



Custom ContentCustom digital animation to attract store traffic, promote brand campaigns and create retail ambiance



LED LightingEfficient, versatile and long lasting light source to maximize your displays investment and operability




Lights Command Attention

Capture attention or create ambiance? Onset of motion, changes in brightness, dramatic color transformations and unique imagery are used in The Window Light Show™ to capture attention and evoke emotion at retail

CODE	DESCRIPTION	LED*	BRIGHTNESS cd/unit**	PITCH***	PCB BAR	PANEL	COLUMN	ROW	TOTAL LED	WIDTH x HEIGHT****
UWLS007	Small	1	2,949	3 cm	12	5	60	64	3,840	1,986 mm X
										2,140 mm
UWLS008	Small	2	2,949	3 cm	12	5	60	64	7,680	1,986 mm X
										2,140 mm
UWLS001	Small	1	737	6 cm	8	4	32	32	1,024	2,046 mm X
										2,082 mm
UWLS002	Small	2	737	6 cm	8	4	32	32	2,048	2,046 mm X
										2,082 mm
UWLS009	Medium	1	3,686	3 cm	12	7	84	64	5,376	2,736 mm X
										2,140 mm
UWLS010	Medium	2	3,686	3 cm	12	7	84	64	10,752	2,736 mm X
										2,140 mm
UWLS003	Medium	1	922	6 cm	8	5	40	32	1,280	2,526 mm X
										2,082 mm
UWLS004	Medium	2	922	6 cm	8	5	40	32	2,560	2,526 mm X
										2,082 mm
UWLS011	Large	1	4,424	3 cm	12	8	96	64	6,144	3,113 mm X
										2,140 mm
UWLS012	Large	2	4,424	3 cm	12	8	96	64	12,288	3,113 mm X
										2,140 mm
UWLS005	Large	1	1,106	6 cm	8	6	48	32	1,536	2,940 mm X
										2,082 mm
UWLS006	Large	2	1,106	6 cm	8	6	48	32	3,072	2,940 mm X
										2,082 mm

^{*}LED = 1 X LED (1 Front) / 2 X LED (1 Front + 1 Back)

^{****} Plus Cable-to-ceiling



^{**} Brightness, cd/unit = candela per square meter/luminance


^{***}Pitch = Distance between LED's (width apart) on PCB Bar

Kinetic Light Show™



At Outform, when we dream it, we do it. We took inspiration from the art and entertainment world and combined it with our passion for dynamic retail and hospitality experiences to create the Kinetic Light Show™. Demanding attention with a unique play of light, color, and motion, the Kinetic Light Show™ creates mesmerizing choreographed visuals that transform ordinary surroundings into works of art.





Choreographed Movement & Color

The Kinetic Light Show performs precise choreographed sequences that leave people amazed. Each LED light globe has a full range of color and luminosity, making the possibilities endless! Whether you're in need of a unique color story or seasonal promotion, the Kinetic has you covered. Full control of height, speed, color, and luminance makes the Kinetic a great choice for any brand, product, or season.



Wow Effect

The Kinetic Light Show wows from afar with stimulating movement and lighting. The result is an increases in dwell time and consideration.



Versatile Applications

With a wide range of applications from retail to hospitality. This display is completely adjustable for specific height requirements, installation needs, and sizes.




Modular

Compose your base units with either one or two rows of lights in a variety of configurations or create larger display matrices for even more visual impact.

System Diagram

The Kinetic Light Show is controlled by a series of wireless sub controllers that coordinate movement with individual LED elements. Each row's sub controller communicates directly to the programmable main controller, enabling both ease-of-use and limited wiring and excessive clutter needed for each display.







Specifications

Item: MB16

Working voltage: AC 100~240V
Power: About 40W
Size: Ф20cm ball
Kinetic distance: < 2M

Kinetic distance: < 2M
Max speed: 0.5 meters per second

LED qty: 16 pcs per ball Wireless control distance: < 15M

* Standard Capacity Battery

Battery capacity: 2,000 mah
Charging time: 4H

Continuous working time: 5H (Color gradually changing effect)

* High Capacity Battery (under development)

Battery capacity: 4,000 mah Charging time: 8H

Continuous working time: 10H (Color gradually changing effect)

* Alternative

Control Mode



K-SY-308-W-KB Wirelss Master Controller

Size: 190L×140W×45H mm

Remote control distance: 20m (Without obstacle)

Wirelss frequency: 2.4GHz
Output port: RJ45×1
Max power: 10W

Working temperature: -15°C~60°C

SD Card: 4G

Cover color: Silver

Working voltage: DC7.5V

Power plug: Power adapter

Capacity: 16 pcs Sub Controller

Function: Change the display effect of the LED

ball wirelessly.

Send the moving style and speed to the LED ball from the repeater by network

cable.



SY-308-KB Sub Controller

Size: 165L×120W×40H mm

Output channel: 1 channels
Output signal: RS-485
Output port: RJ45*1
Max power: 5W

Working temperature: $-15^{\circ}\text{C}\sim60^{\circ}\text{C}$ Cover color: Black

Working voltage: AC110V/220V


Power plug: By customer's request

Capacity: 16 pcs LED Ball

Function: Process the motion command of

the main-controller and control the stepper motor on the top tray.

System Diagram



Product unit list

Item	Description	Order Quantity	Unit
LED Ball	Including the control box, carton box	1-49	Set
LED Ball	Including the control box, carton box	50-299	Set
LED Ball	Including the control box, carton box	300-999	Set
LED Ball	Including the control box, carton box	More than 1,000	Set
Main Controller	Max for 16pcs sub controller including software		PC
Sub Controller	Max for 16pcs LED Ball		PC

Kinetic LED Light Show™ Model Number: ULKS001

One row, 2 meters

Item	Description	Order Quantity	Unit
LED Ball	Including the control box	5	Set
Main Controller	Including software	1	PC
Sub Controller	One for 5pcs LED Ball	1	PC
Top plate	Iron, spray painting, including wooden case. The price is estimated.	1	Set



 ${\sf Kinetic\ LED\ Light\ Show^{\scriptscriptstyle\mathsf{TM}}\ Model\ Number:\ ULKS003}$

One row, 2.5 meters

Item	Description	Order Quantity	Unit
LED Ball	Including the control box	6	Set
Main Controller	Including software	1	PC
Sub Controller	One for 6pcs LED Ball	1	PC
Top plate	Iron, spray painting, including wooden case. The price is estimated.	1	Set



Kinetic LED Light Show $^{\text{\tiny TM}}$ Model Number: ULKS005

One row, 3 meters

ltem	Description	Order Quantity	Unit
LED Ball	Including the control box	7	Set
Main Controller	Including software	1	PC
Sub Controller	One for 7pcs LED Ball	1	PC
Top plate	Iron, spray painting, including wooden case. The price is estimated.	1	Set



Kinetic LED Light Show™ Model Number: ULKS002

Two rows, 2 meters

Item	Description	Order Quantity	Unit
LED Ball	Including the control box	10	Set
Main Controller	Including software	1	PC
Sub Controller	One for two rows, 10 pcs LED Ball	1	PC
Top plate	Iron, spray painting, including wooden case. The price is estimated.	1	Set



Kinetic LED Light Show™ Model Number: ULKS004

Two rows, 2.5 meters

Item	Description	Order Quantity	Unit
LED Ball	Including the control box	12	Set
Main Controller	Including software	1	PC
Sub Controller	One for two rows, 12 pcs LED Ball	1	PC
Top plate	Iron, spray painting, including wooden case. The price is estimated.	1	Set



Kinetic LED Light Show™ Model Number: ULKS006

Two rows, 3 meters


Item	Description	Order Quantity	Unit
LED Ball	Including the control box	14	Set
Main Controller	Including software	1	PC
Sub Controller	One for two rows, 14 pcs LED Ball	1	PC
Top plate	Iron, spray painting, including wooden case. The price is estimated.	1	Set



Kinetic LED Light Show™ Model Number: ULKS101

Matrix, 2 x 2 meters


ltem	Description	Order Quantity	Unit
LED Ball	Including the control box	25	Set
Main Controller	Including software	1	PC
Sub Controller	One for two rows, 10 pcs LED Ball	3	PC
Trestle	Iron, spray painting, truss support, including wooden case packing. The price is estimated.	1	Set



Kinetic LED Light Show™ Model Number: ULKS102

Matrix, 3 x 3 meters


Item	Description	Order Quantity	Unit
LED Ball	Including the control box	49	Set
Main Controller	Including software	1	PC
Sub Controller	One for two rows, 14 pcs LED Ball	4	PC
Trestle	Iron, spray painting, truss support, including wooden case packing. The price is estimated.	1	Set



Kinetic LED Light Show™ Model Number: ULKS103

Matrix, 4 x 4 meters

Item	Description	Order Quantity	Unit
LED Ball	Including the control box	100	Set
Main Controller	Including software	1	PC
Sub Controller	One for one row, 10 pcs LED Ball	10	PC
Trestle	Iron, spray painting, truss support, including wooden case packing. The price is estimated.	1	Set





BY OUTFORM...



Product Catalog







Enterprise



4K Media Player



Tower



iShelf



Window Light Show™



Kinetic LED Light Show™